

Heavy Vehicle Specialist Certificate

Must be presented to a Transport Service Delivery Agent Heavy Vehicle Specialist Inspector and Inspecting Organisation

21.00	SUTTON			BJS
ehicle Registration*	VIN / Chassis			023198
component being certified:		sis Modification ng Connection	Load Anchorage	Log Bolster
Certification Category HVS 2		Stability	PSV Rollover	Swept Path
Description of Work Cer	tily SRT-	5axle	full T	ailer
		\supset		
Million Processing Charles and Control of State				
			and the second	
ode/Standard Certified to VZTA Rule 4100	1:2002		Load Rating(s) 4-25m / Y	1=29T
eneral Drawing Number(s)		Y2 =	33T / X2	l= 4.05m
unantina Decuments		Load T	pe: Unifor	in Deneity
SRT	Complian			
SRT Special Conditions	Above	re Ce	4 # \$570	
SRT Special Conditions	Above	ce Ce	+ # 3570	
pecial Conditions As ertification Expiry Date (if applicable) Declaration	Above	or Hutodomet	+ # 3570	comes first)
pecial Conditions ertification Expiry Date (if applicable) Declaration the undersigned, declare that I are specialist Inspector identified above alid appointment. I certify that the	m the Heavy Vehicle we and I hold a current he above mentioned vehicle	Or Hubodomet	er Reading (whichever	comes first)
pecial Conditions As Pertification Expiry Date (if applicable) Declaration the undersigned, declare that I are specialist Inspector identified above alid appointment. I certify that the component's design, manufacture certification complies in all respectors.	m the Heavy Vehicle we and I hold a current ne above mentioned vehicle and installation, and this ts with the Land Transport	Or Hubodomet Designer's I	er Reading (whichever	comes first) coturer)
opecial Conditions Assembly Date (if applicable)	m the Heavy Vehicle we and I hold a current ne above mentioned vehicle and installation, and this ts with the Land Transport to 2002 and my Deed of nowledge the information	Or Hubodomet Designer's I Inspector's "Delegate's	er Reading (whichever of the state of the st	comes first) coturer)

PHONE 07 575 5139 07 575 5137



www.domett-trailers.co.nz

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Address:

SRT Compliance Certificate no:

S570

Vehicle Identification No.(VIN):

7A9E25017D1023198

Vehicle chassis No:

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

No of axles in rear set:

Deck length of vehicle:

10.36 metres

Maximum height of load or vehicle body:

4.25 metres

Front suspension type:

User Defined

Rear suspension type:

User Defined

I, Bruce Sutton of Domett Truck and Trailer, PO Box 5215, Mt Maunganui certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max, load height of 4.25 metres and a max, allowable gross mass of 33 tonnes, the SRT is 0.33g This vehicle fails to meet the minimum SRT standard of 0.35g. It will meet the standard if:

- At maximum load height of 4.25 metres, the maximum allowable gross mass is 29.3 tonnes.
- At maximum gross mass of 33 tonnes, the maximum allowable load height is 4.05 metres. or (b)

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)
1 33 7 E g	4.05
32	4.1
31	4.15
30	4.2
29	4.25

Note: Calculated load heights greater than the legal limit of 4.25m have been set to 4.25m

Results of SRT test to be displayed on Certificate of Loading	7% W 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
X1 = 4.25 metres / Y1 = 29 tonnes; Y2 = 33 tonnes / X2 = 4.0)5 metres.

The type of test carried out to establish this rating was: LTSA SRT Calculator Version 1.32c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19.5	Dual
4	19.5	Dual
5	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs ; p	Front is	Rear
Gross mass (kg):	15000	18000
Payload mass (kg):	12260	14860
Tare mass (kg):	2740	3140
Average load bed height (m):	1.06	
Average load height (m):	4.25	
Suspension type:	User Defined	User Defined
Suspension track width (m):	0.94	0.94
Lash (mm):	90 ==	II 90 ()
Suspension brand/model:	SAF INTRADISC IU28/2005RZ	SAF INTRADISC IU28/2005RZ
Roll stiffness/axle (Nm/radian):	1200000	1200000
Spring stiffness/spring (N/m):	470000	470000
Roll centre height from axle (m):	0.05	0.05

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule. Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Vehicle Inspector/Inspecting Organisation No BJS

SRT Compliance Certificate no.

Name: Bruce Sutton

Date: 7/10/2013

S570

ETB - ES PTF