

STATEMENT OF COMPLIANCE WITH THE NEW ZEALAND HEAVY VEHICLE BRAKE CODE

VEHICLE TYPE : SEMI-TRAILER
 MAKE : DOMETT MODEL : B2003
 SERIAL NUMBER : 150 GVM (on road) : 23000
 GVM (off road) : N/A GCM : N/A
 UNLADEN CoG HEIGHT : 0.000 WHEELBASE : 0.000
 UNLADEN MASS, FRONT : 14.50 UNLADEN MASS, REAR : 0.000
 PAYLOAD : 0.000
 PAYLOAD CoG HEIGHT : 0.000 POSITION : 0.000 RANGE : N/A
 REAR SUSPENSION TYPE : DUAL AXLE
 REACTIVE/NONREACTIVE : NON REACTIVE

SYSTEM PRESSURE:

MAXIMUM OPERATING Pm : N/A
 GOVERNOR CUTIN Pg : N/A
 TIME Pg to Pm : N/A

AXLE	COUPLING THRESHOLD kPa	BRAKE FORCE kN/kPa	TYRE SIZE mm	FRICTION MATERIAL		
				MAKE	ID NUMBER	COF
1	64.33	0.078	400.0	JURID	539	0.410
2	64.33	0.078	400.0	JURID	539	0.410


AXLE	BRAKE TYPE	DRUM DIAMETER	CHAMBER SIZE	SLACK LENGTH	SPRING FORCE
1	BPW DISK	754.0	118.0	76.00	5.940
2	BPW DISK	754.0	118.0	76.00	5.940

TRAILER

VALVE TYPE	MAKE	MODEL/VERSION
RELAY 1	SEALCO	110415
RELAY 2	-	-
SPRING BRAKE VALVE	SEALCO	110170
QUICK RELEASE VALVE	-	-
PILOT	-	-
OTHER	-	-
OTHER	SEALCO	17600B

I, the undersigned do hereby certify that the vehicle identified above complies with all requirements of the current New Zealand Heavy Vehicle Brake Code.

Date : 4 OCT 99

Signed : 

Certifier's Identification

Name : B.R. LAING

Phone : (09)9807300

Company : TRANSPORT SPECIALTIES LTD

Postal Address : CNR ASH & KERRS RDS
 : WIRI AUCKLAND
 : PO BOX 98-971 S.A.M.C

Fax : (09)9807306

Position : LTSA CERTIFIER #1055

Modification

I, the undersigned do hereby re-certify the vehicle identified above, as modified complies with all requirements of the current New Zealand Heavy Vehicle Brake Code.

Date :

Signed :

Certifier's Identification

Name :

Phone :

Company :

Postal Address :

Fax :

Position :

9910819 DOMETT CHASSIS 150

VEHICLE TYPE : SEMI-TRAILER

REAR SUSPENSION TYPE : DUAL AXLE

LADEN MASS ON THE REAR SUSPENSION OF THE VEHICLE : 14.50 tonnes

AXLE TYPE	NO. OF VALVES	RATIO VALVE	INSHOT PRESSURE	RATIO OUT/IN	COUPLING PRESSURE 100Nm DRUM TORQUE
1	1	0	0.000	0.000	64.33

AXLE TYPE	VALVE NO.	CRACKING PRESSURE	PRESSURE IN kPa	PRESSURE OUT kPa
1	1	31.00	650.0	650.0

AXLE TYPE	LINING CoF	CHAMBER AREA cm ²	ADJUSTER LENGTH mm	TYRE RADIUS mm	BRAKE DRUM RADIUS mm
1	0.410	118.0	76.00	400.0	377.0

AXLE TYPE	CHAMBER (1) PRESSURE kPa	DRUM (1) TORQUE kNm	CHAMBER (2) PRESSURE kPa	DRUM (2) TORQUE kNm
1	35.00	0.100	650.0	9.300

VEHICLE BRAKE FORCE/TONNE AT 500kPa = 4.79kN/tonne

AXLE NO.	AXLE TYPE	EMERGENCY PRESSURE kPa	PARKING FORCE kN
1	1	490.0	5.940
2	1	490.0	5.940

STOPPING DISTANCE FOR EMERGENCY PRESSURE = 7.29 m

STOPPING DISTANCE FOR SPRING BRAKES = 7.08 m

THE PARKING BRAKES WILL HOLD THE VEHICLE ON A 1 IN 1.73 SLOPE

9910819 DOMETT CHASSIS 150

