

Heavy vehicle specialist certificate Must be presented to a CoF (heavy) inspecting organisation if not entered into LANDATA

				ISH	
		11 11 IN 12	10.12	12 14 15	- 17
		Chassis]0]2	-	
Log bolsters		Towing connection	on	Brakes	
		PSV stability		PSV rol	lover
TRAILER					
			: 29t		Archine consequence
	Y2 = 32t / X2 = 4.17m				
266	-contented-to-to-to-to-to-to-to-to-to-to-to-to-to-			actions to the security to the second	
samann population s van company and app		7.7.7.7 Marita (17.5.200 Aug 17.200 Aug 17.2		Truck of the state	
or	Hubodomete	er reading (whichever con	nes first)		
	Designer's ID) (if different from inspector i	below)		1
l gn, ss ards	Inder	geet Singh ame (PRINT IN CAPS) RJEET SINGH	mber	ISF	- American
	A 9 D Component being Log bolsters SRT Swept path TRAILEF	Component being certified: Log bolsters SRT Swept path TRAILER Component X1 = Y2 = LOAE Posigner's ID Inspector's si Inspector's si Inspector's ni INDER	Component being certified: Log bolsters Chassis Towing connection SRT PSV stability PBS TRAILER Component load rating(s) X1 = 4.30m / Y1 = Y2 = 32t / X2 = 4. LOAD TYPE: UNI Component load rating (whichever component load rating (s) X1 = 4.30m / Y1 = Y2 = 32t / X2 = 4. LOAD TYPE: UNI Component load rating (s) Inspector's signature Inspector's signature Inspector's name (PRINT IN CAPS) INDERJEET SINGH	Component being certified: Chassis Towing connection SRT PSV stability Swept path PBS Component load rating(s) X1 = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM PSS Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) Load I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) Load I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating(s) Load I = 4.30m / Y1 = 29t Y2 = 32t / X2 = 4.17m LOAD TYPE: UNIFORM Component load rating	Component being certified: Log bolsters Towing connection Brakes SRT PSV stability PSV roll Swept path Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI PSV roll Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) X1 = 4.30 m / Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: UNIFORM DENSI Component load rating(s) Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: Uniform load rating(s) Component load rating(s) Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: Uniform load rating(s) Component load rating(s) Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: Uniform load rating(s) Component load rating(s) Y1 = 29t Y2 = 32t / X2 = 4.17 m LOAD TYPE: Uniform load rating(s) Component load rating(s) Y2 = 32t / X2 = 4.17 m LOAD TYPE: Uniform load rating(s) Component load rating(s) Load Type load rating(

All fields are mandatory unless otherwise stated.

New	72		

Static Roll Threshold Compliance Certificate

Name of vehicle owner: Exclusive Transport & Boat

Haulage Ltd

Address:

SRT Compliance Certificate no: S1266

Vehicle Identification No.(VIN): 7A9D20011N2023157

Vehicle chassis No: 2157

Current vehicle registration:

Type of vehicle: Full-Trailer

No of axles in front set: 2 No of axles in rear set: 2

Deck length of vehicle: 10.20 metres

Maximum height of load or vehicle body: 4.30 metres

Front suspension type: User Defined

Rear suspension type: User Defined

I, Inderjeet Singh of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142 certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically

between load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 32 tonnes, the SRT is 0.34g This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.3 metres, the maximum allowable gross mass is 29.6 tonnes.
- or (b) At maximum gross mass of 32 tonnes, the maximum allowable load height is 4.17 metres. The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)	
32	4.17	
31	4.23	
30	4.27	
29	4.3	

Note: Calculated load heights greater than the legal limit of 4.30m have been set to 4.30m

Results of SRT test to be displayed on Certificate of Loading	
X1 = 4.3 metres / Y1 = 29 tonnes; $Y2 = 32 tonnes / X2 = 4.17 metres$.	

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19.5	Dual
4	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear	
Gross mass (kg):	16000	16000	
Payload mass (kg):	12760 12880		
Tare mass (kg):	3240	3120	
Average load bed height (m):	1.073		
Average load height (m):	4.30		
Suspension type:	User Defined	User Defined	
Suspension track width (m):	0.994	0.994	
Lash (mm):	0	0	
Suspension brand/model:	Hendrickson Intraax AANL ZMD	Hendrickson Intraax AANL ZMD	
Roll stiffness/axle (Nm/radian):	1824776	1824776	
Spring stiffness/spring (N/m):	350000	350000	
Roll centre height from axle (m):	0.051	0.051	

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed: Inderject Singh
Vehicle Inspector/Inspecting Organisation No ISH

Name: Inderjeet Singh

Date: 8/3/2022

SRT Compliance Certificate no:

S1266

Print the Certificate

Finish