

Heavy vehicle specialist certificate Must be presented to a CoF (heavy) inspecting organisation if not entered into LANDATA

Heavy vehicle specialist inspector's or manufacturing CAMERON HARRIS	inspecting organisation's name (PRINT IN CAPS)	ID CNH
Plate number (optional) Make DOMETT	VIN/chassis number 7 A 9 E 2 5 0 1 4 Component being certified: Chass	N 2 0 2 3 2 0 4 Load anchorage
Model (optional 2022 E2501 H Certification category HVS2 Description of work CERTIFY SRT - 5 AXLE FUL	Log bolsters Towin X SRT PSV s Swept path PBS	g connection Brakes tability PSV rollover
Code/standard/rule certified to NZTA RULE 41001:2016 General drawing number(s) Supporting documents SRT COMPLIANCE CERT # S		
Special conditions (optional) AS ABOVE		
Declaration I the undersigned, declare that I am the heavy vehicle inspector identified and I hold a current valid appointr certify that the above mentioned vehicle component's manufacture and installation, and this certification coin all respects with the Land Transport Rule: Vehicle St Compliance 2002 and my appointment. To the best of knowledge the information contained in the certificate and correct.	nent. I design, nplies andards my Inspector's signature Inspector's name (PRINT) CAMERON I	from inspector below)
		021130

All fields are mandatory unless otherwise stated.

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Stocklines Ltd

Address:

SRT Compliance Certificate no:

S1313

Vehicle Identification No.(VIN):

7A9E25014N2023204

Vehicle chassis No:

2204

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

2

No of axles in rear set:

3

Deck length of vehicle:

11.28 metres

Maximum height of load or vehicle body:

4.3 metres

Front suspension type:

Generic Air High Stiffness

Rear suspension type:

Generic Air High Stiffness

I, Cameron Harris of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142 certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type:

Uniform density

Description:

Assumes load mass is centred midway vertically between

load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 35 tonnes, the SRT is 0.32g

This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.3 metres, the maximum allowable gross mass is 27.7 tonnes.
- or (b) At maximum gross mass of 35 tonnes, the maximum allowable load height is 3.9 metres. The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)	
35	3.9	
34	3.95	
33	4	
32	4.05	
31	4.09	
30	4.15	
29	4.21	
28	4.27	
27	4.3	

Note: Calculated load heights greater than the legal limit of 4.30m have been set to 4.30m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.3 metres / Y1 = 27 tonnes; Y2 = 35 tonnes / X2 = 3.9 metres.

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	17.5	Dual
2	17.5	Dual
3	17.5	Dual
4	17.5	Dual
5	17.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear
Gross mass (kg):	16000	19000
Payload mass (kg):	13220	15780
Tare mass (kg):	2780	3220
Average load bed height (m):	0.94	
Average load height (m):	4.3	
Suspension type:	Generic Air High Stiffness	Generic Air High Stiffness
Suspension track width (m):	0.98	0.98
Lash (mm):	95	95

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Name: Cameron Harris

Vehicle Inspector/Inspecting Organisation No CNH

Date: 14/12/2022

SRT Compliance Certificate no:

S1313