

Heavy vehicle specialist certificate

Must be presented to a CoF (heavy) inspecting organisation if not entered into LANDATA

Heavy vehicle specialist inspector's or manufacturing inspe GERRIT VISAGIE	ecting organisa	ation's name (PRII	NT IN CAPS)	GV GV	
Plate number (optional) VIN 7	/chassis num		1 3 P 2 0	0 2 3 2 7 8	3
Make DOMETT Co	mponent bein	g certified:	Chassis	Load anchor	
Model (optio 2023 E2001 PH33	Log bolsters		Towing connection		
Certification category HVS2	SRT		PSV stability	PSV rollover	
Description of work	Swept path		PBS		
CERTIFY SRT - 5 AXLE FULL	TRAILE	R			energeney, were returned particular to the second
Code/standard/rule certified to NZTA RULE 41001:2016		Component	load rating(s) 4.30m / Y1 = 3		A STATE OF THE PROPERTY OF THE
	1		4.30m / Y1 = 3 35t / X2 = 4.22		- Commence
General drawing number(s)	and the state of t			ORM DENSITY	Toward Commen
Supporting documents SRT COMPLIANCE CERT # S136	61				pharman, protest
Special conditions (antional) AS ABOVE	NASSENIUS (1932 1942 Listenius Abdulateur)	enters in the case of the contents of section of the contents			- American American
Certification expiry date (if applicable)	or	Hubodomete	er reading (whichever comes	first)	Tarrison .
Declaration		Designer's ID	(if different from inspector belo	ow)	, and
I the undersigned, declare that I am the heavy vehicle special inspector identified and I hold a current valid appointment. I certify that the above mentioned vehicle component's design manufacture and installation, and this certification complies in all respects with the Land Transport Rule: Vehicle Standar Compliance 2002 and my appointment. To the best of my knowledge the information contained in the certificate is true and correct.	I s rds	Inspector's name of the sector's name of the sector	ame (PRINT IN CAPS) IT VISAGIE	G V ber 856185	variable administration and sections of the section
CoF vehicle inspector ID (if applicable) CoF ve	ehicle inspecto	or signature (if apı	plicable) Date		

All fields are mandatory unless otherwise stated.

Static Roll Threshold Compliance Certificate

Name of vehicle owner:

Booths Transport

Address:

SRT Compliance Certificate no:

S1361

Vehicle Identification No.(VIN):

7A9E20013P2023278

Vehicle chassis No:

2278

Current vehicle registration:

Type of vehicle:

Full-Trailer

No of axles in front set:

2

No of axles in rear set:

3

Deck length of vehicle:

12.190 metres

Maximum height of load or vehicle body:

4.3 metres

Front suspension type:

User Defined

Rear suspension type:

User Defined

I, Gerrit Visagie of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142 certify that

at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type:

Uniform density

Description:

Assumes load mass is centred midway vertically between

load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 35 tonnes, the SRT is 0.34g

This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

- (a) At maximum load height of 4.3 metres, the maximum allowable gross mass is 33.4 tonnes.
- or (b) At maximum gross mass of 35 tonnes, the maximum allowable load height is 4.22 metres. The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)
35	4.22
34	4.26
33	4.3

Note: Calculated load heights greater than the legal limit of 4.30m have been set to 4.30m

Results of SRT test to be displayed on Certificate of Loading		
X1 = 4.3 metres / Y1 = 33 tonnes; $Y2 = 35 tonnes / X2 = 4.22 metres$.		

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:	
1	19.5	Dual	
2	19.5	Dual	
3	19.5	Dual	
4	19.5	Dual	
5	19.5	Dual	

Body Style is Standard

Mass and Suspension Data:

Inputs	Front	Rear	
Gross mass (kg):	16000	19000	
Payload mass (kg):	12840	14980	
Tare mass (kg):	3160	4020	
Average load bed height (m):	1.070		
Average load height (m):	4.3		
Suspension type:	User Defined	User Defined	
Suspension track width (m):	.994	.994	
Lash (mm):	0	0	
Suspension brand/model:	nd/model: Hendrickson Intraxx AANL ZMD		
Roll stiffness/axle (Nm/radian):	1824776	1824776	
Spring stiffness/spring (N/m):	350000	350000	
Roll centre height from axle (m):	0.051	0.051	

I certify that I am a vehicle inspector appointed under section 2 of Land Transport Rule: Vehicle Standards Compliance 2002. I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed:

Vehicle Inspector/Inspecting Organisation No GV

SRT Compliance Certificate no:

Name: Gerrit Visagie

Date: 18/7/2023

S1361