

Heavy vehicle specialist inspector's or manufacturing inspecting organisation's name (PRINT IN CAPS)

CAMERON HARRIS

ID

CNH

Plate number (optional)

VIN/chassis number

7 A 9 C 2 0 0 3 8 T 2 0 2 3 5 7 1

Make

DOMETT

Component being certified:

☐ Chassis

☐ Load anchorage

Model (optional)

C2003 PH

☐ Log bolsters

☐ Towing connection

☐ Brakes

Certification category

HVS2

☒ SRT

☐ PSV stability

☐ PSV rollover

☐ Swept path

☐ PBS

Description of work

CERTIFY SRT - 3 AXLE SEMI TRAILER

Code/standard/rule certified to

NZTA RULE 41001:2016

Component load rating(s)

X1 = 4.30m / Y1 = 19t

Y2 = 19t / X2 = 4.30m

LOAD TYPE: UNIFORM DENSITY

General drawing number(s)

Supporting documents

SRT COMPLIANCE CERT # S1566 A&B

S1566A (Front Unit Only) X1=4.3m / Y1=16t ; Y2=19t / X2=4.06m

Special conditions (optional)

AS ABOVE

Certification expiry date (if applicable)

or

Hubodometer reading (whichever comes first)

Declaration

I the undersigned, declare that I am the heavy vehicle specialist inspector identified and I hold a current valid appointment. I certify that the above mentioned vehicle component's design, manufacture and installation, and this certification complies in all respects with the Land Transport Rule: Vehicle Standards Compliance 2002 and my appointment. To the best of my knowledge the information contained in the certificate is true and correct.

Designer's ID (if different from inspector below)

Inspector's signature



Inspector's name (PRINT IN CAPS)

CAMERON HARRIS

ID number

C N H

Date

08-09-2026

Number

H 02634

CoF vehicle inspector ID (if applicable)

CoF vehicle inspector signature (if applicable)

Date

Static Roll Threshold Compliance Certificate

Name of vehicle owner:	Talleys Group		
Address:			
SRT Compliance Certificate no:	S1566B		
Vehicle Identification No.(VIN):	7A9C20038T2023571		
Vehicle chassis No:	2571		
Current vehicle registration:			
Type of vehicle:	Semi-Trailer		
No of axles in front set:	0	No of axles in rear set:	3
Deck length of vehicle:	7.7 metres		
Maximum height of load or vehicle body:	4.3 metres		
Front suspension type:	none		
Rear suspension type:	User Defined		

I, **Cameron Harris of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142** certify that at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 19 tonnes, the SRT is 0.36g

This vehicle meets or exceeds the minimum SRT target of 0.35g.

Results of SRT test to be displayed on Certificate of Loading
X1 = 4.3 metres / Y1 = 19 tonnes ; Y2 = 19 tonnes / X2 = 4.3 metres.

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Rear
Gross mass (kg):	19000
Payload mass (kg):	12510
Tare mass (kg):	6490
Average load bed height (m):	1.27
Average load height (m):	4.3
Suspension type:	User Defined
Suspension track width (m):	0.94
Lash (mm):	90
Suspension brand/model:	SAF IU25
Roll stiffness/axle (Nm/radian):	1200000
Spring stiffness/spring (N/m):	470000
Roll centre height from axle (m):	0.05

I certify that I am a vehicle inspector appointed under *section 2 of Land Transport Rule: Vehicle Standards Compliance 2002*.
I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed: 

Vehicle Inspector/Inspecting Organisation No **CNH**

SRT Compliance Certificate no:

Name: **Cameron Harris**

Date: **8/9/2026**

S1566B

Static Roll Threshold Compliance Certificate

Name of vehicle owner: Talleys Group

Address:

SRT Compliance Certificate no: S1566A

Vehicle Identification No.(VIN): 7A9C20038T2023571

Vehicle chassis No: 2571

Current vehicle registration:

Type of vehicle: Semi-Trailer

No of axles in front set: 0 No of axles in rear set: 3

Deck length of vehicle: 7.7 metres

Maximum height of load or vehicle body: 4.3 metres

Front suspension type: none

Rear suspension type: User Defined

I, **Cameron Harris of Domett Truck and Trailer, PO Box 9458, Greerton, Tauranga 3142** certify that at the time of inspection this vehicle achieved a rating on a Static Roll Threshold test as follows:

Using standard load type: Uniform density Description: Assumes load mass is centred midway vertically between load bed and load height.

At a max. load height of 4.3 metres and a max. allowable gross mass of 19 tonnes, the SRT is 0.33g

This vehicle fails to meet the minimum SRT target of 0.35g. It will meet the standard if:

(a) At maximum load height of 4.3 metres, the maximum allowable gross mass is 16.5 tonnes.

or (b) At maximum gross mass of 19 tonnes, the maximum allowable load height is 4.06 metres.

The vehicle achieves the minimum SRT of 0.35g at the following weight and height combinations:

Gross Mass (tonnes)	Load Height (m)
19	4.06
18	4.15
17	4.24
16	4.3

Note: Calculated load heights greater than the legal limit of 4.30m have been set to 4.30m

Results of SRT test to be displayed on Certificate of Loading

X1 = 4.3 metres / Y1 = 16 tonnes ; Y2 = 19 tonnes / X2 = 4.06 metres.

The type of test carried out to establish this rating was: NZTA SRT Calculator Version 2.12c

Summary Input Data used for calculation.

Tyre Data:

Axle	Tyre Size:	Tyre Configuration:
1	19.5	Dual
2	19.5	Dual
3	19.5	Dual

Body Style is Standard

Mass and Suspension Data:

Inputs	Rear
Gross mass (kg):	19000
Payload mass (kg):	15210
Tare mass (kg):	3790
Average load bed height (m):	1.27
Average load height (m):	4.3
Suspension type:	User Defined
Suspension track width (m):	0.94
Lash (mm):	90
Suspension brand/model:	SAF IU25
Roll stiffness/axle (Nm/radian):	1200000
Spring stiffness/spring (N/m):	470000
Roll centre height from axle (m):	0.05

I certify that I am a vehicle inspector appointed under *section 2 of Land Transport Rule: Vehicle Standards Compliance 2002*.
I certify that this certificate complies in all respects with the applicable requirements in that rule, and that, to the best of my knowledge, the information in this certificate is true and correct

Signed: 

Vehicle Inspector/Inspecting Organisation No **CNH**

SRT Compliance Certificate no:

Name: **Cameron Harris**

Date: **8/9/2026**

S1566A

Domett Truck & Trailer Ltd
Taurikura Drive & Kennedy Road
Tauriko, Tauranga

PDS



Date: 8/09/2026

Job Number: 11200

Certifier: Cameron Harris

ID: CNH

Client: Talleys Group

Vehicle Details

Make:	Domett	Model:	C2003 PH	Trailer GVM:	33000 kg
VIN number:	7A9C20038T2023571	Chassis Number:	2571	Rego:	
				Hubo:	

Standards / Codes the design must comply with

Vehicle Dimensions & Mass (41001)

√

Component

SRT

√

X1 4.3 m

Y1 19 t

Y2 19 t

X2 4.3 m

Certificate # S1566 A&B

Load Type Uniform Density

LT400

LT400 # H02634

Category HVS2

File Content

Vehicle Info	Y	N
Photographs	Y	N
Drawings	Y	N
Proprietary component data	Y	N
Calculations	Y	N
LT400	Y	N

Certify

YES

NO

I declare that I am a heavy vehicle specialist certifier – engineer and I hold a current valid appointment. I certify that this vehicle component design and this certification comply in all respects with the Land Transport Rule: Vehicle Standards Compliance 2002; my Notice of Appointment and applicable requirements. To the best of my knowledge the information contained in this certificate is true and correct.

Certifier Signature:

Date:

8/09/2026

Domett Truck & Trailer Ltd
Taurikura Drive & Kennedy Road
Tauriko, Tauranga

SRT Worksheet



Date: 8/09/2026

Job Number: 11200

Certifier: Cameron Harris

ID: CNH

Client: Talleys Group

Cert #: S1566 A&B

Vehicle Details

Make:	Domett	Model:	C2003 PH	Trailer GVM:	33000 kg
VIN number:	7A9C20038T2023571	Chassis Number	2571	Rego:	
				Hubo:	

Suspension Details

Make:	SAF	Model:	IU25/2000RZ-68A	Fixed	N/A
Ride Height:	230 mm			Steerer	N/A

Suspension data referenced in File "Design info SRT's", in Engineering office.

Dolly

Number of Axles	0	Hanger Centres - Dolly	0
Tyre Size	N/A	Tyre Configuration	N/A

Fixed

Number of Axles	3	Hanger Centres - Fixed	940 mm
Tyre Size	265/70 R 19.5	Tyre Configuration	Dual

Steerers

Number of Axles	0	Hanger Centres - Steerers	0
Tyre Size	265/70 R 19.5	Tyre Configuration	Dual

Load Details

Uniform Density ☒

Mixed Freight ☐

Other ☐

Masses		Front	Rear	Total
Gross:		kg	19,000.00 kg	19,000.00 kg
Tare:		3,080.00 kg	3,790.00 kg	6,870.00 kg
Load Height Max:	4.30 m	Payload Cog:		m
Deck Length:	7.70 m	Max Height:		4.30 m
Front Deck Height:	1.42 m	Front Deck Length:		4,410.00 m
Rear Deck Height:	1.06 m	Rear Deck Length:		3,310.00 m
		Average:		1.27 m